

# Installation Printers in Debian

## Brother driver installation

Download the “Driver Installation tool” from:

[https://support.brother.com/g/b/downloadend.aspx?c=nl&lang=nl&prod=mfc9330cdw\\_us\\_eu\\_as&os=128&dlid=dlf006893\\_000&flang=4&type3=625](https://support.brother.com/g/b/downloadend.aspx?c=nl&lang=nl&prod=mfc9330cdw_us_eu_as&os=128&dlid=dlf006893_000&flang=4&type3=625)

The current Brother driver is a 32-bit version and will give error during installation (Package ia32-libs is not available). This package is depreciated and needs to be replaced by alternative.

```
apt-get install lib32z1
apt-get install cups
```

## Unwanted Printer discovery

The printer selection dialog of GTK applications is populated by \*directly\* browsing the DNS-SD broadcasts of the remote print server and IPP printers. Whether cups is running or not, this is what happens. In fact, neither CUPS nor cups-browsed is required for the GTK print dialog to function as designed.

Suppose cups-browsed is running with its default cups-browsed.conf. It too will browse the same DNS-SD broadcasts and also populate the dialog, leading to duplicate entries. This is what is observed in Comment 9. If you really, really want cups-browsed, these duplicate entries can be removed by using the filtering facility available in cups-browsed.conf.

From:  
<https://wiki.oscardegroot.nl/> - HomeWiki



Permanent link:  
<https://wiki.oscardegroot.nl/doku.php?id=linux:debian:brother-printer&rev=1641922526>

Last update: **2022/01/15 11:38**