

Systemd-resolved

Systemd-resolved provides resolver services for Domain Name System (DNS).

Status

To check the DNS currently in use by systemd-resolved, run `resolvectl status`.

```
# resolvectl status
-----
Global
    Protocols: +LLMNR +mDNS -DNSOverTLS DNSSEC=no/unsupported
resolv.conf mode: stub

Link 2 (eth0)
    Current Scopes: DNS LLMNR/IPv4 LLMNR/IPv6
        Protocols: +DefaultRoute +LLMNR -mDNS -DNSOverTLS
DNSSEC=no/unsupported
Current DNS Server: fdaa:66:67:a::1
    DNS Servers: fdaa:66:67:a::1
-----
```

Configure

Supporting /etc/resolv.conf

To provide domain name resolution for software that reads `/etc/resolv.conf` directly, such as web browsers, systemd-resolved has four different modes for handling the file—stub, static, uplink and foreign. They are described in `systemd-resolved(8)`. The recommended mode, is the stub mode which uses `/run/systemd/resolve/stub-resolv.conf`. `/run/systemd/resolve/stub-resolv.conf` contains the local stub 127.0.0.53 as the only DNS server and a list of search domains. This is the recommended mode of operation that propagates the systemd-resolved managed configuration to all clients.

```
# ls -al resolv.conf
lrwxrwxrwx 1 root root 37 aug 13 07:27 resolv.conf ->
/run/systemd/resolve/stub-resolv.conf

# cat /run/systemd/resolve/stub-resolv.conf
nameserver 127.0.0.53
options edns0 trust-ad
search .
```

Last update:

2023/08/15 14:17 linux:system:systemd-resolved https://wiki.oscardegroot.nl/doku.php?id=linux:system:systemd-resolved&rev=1692109073

The resolver can be configured by editing /etc/systemd/resolved.conf and/or drop-in .conf files in /etc/systemd/resolved.conf.d/

Links

- <https://wiki.archlinux.org/title/systemd-resolved>

From:

<https://wiki.oscardegroot.nl/> - HomeWiki

Permanent link:

<https://wiki.oscardegroot.nl/doku.php?id=linux:system:systemd-resolved&rev=1692109073>

Last update: **2023/08/15 14:17**

