

Debian Networking

On a typical Debian-based distribution, you have three major packages available for that purpose:

- ifupdown (daemon: networking)
- NetworkManager
- systemd (daemon: systemd-networkd)

In general, you should choose one and stick to it, even if ifupdown works well with NetworkManager it can still create unexpected configuration issues.

ifupdown

Quite deprecated but reliable, you might encounter it on many older systems. The config is stored in **/etc/network/interfaces** and managed by the **networking.service** daemon which is a wrapper around the ifup and ifdown commands which are also wrappers themselves around ifconfig (or ip for ifupdown2).

NetworkManager

Usually included with desktop distributions since many graphical front-ends are available, the config is stored in **/etc/NetworkManager** and managed by the NetworkManager.service daemon.

You can manage the config with the included nmcli or nmtui utilities.


systemd-networkd

Usually used on server distributions and the official successor to ifupdown as it is included within systemd, the config is stored in **/etc/systemd/network** and managed by the systemd-networkd.service daemon.

Read the man at `systemd-networkd. dhclient`

Although not a daemon, dhclient from isc-dhcp-client is nonetheless a very important package and often required on desktop distributions as you often need to obtain a IPv4 from a DHCP server.

Hopefully, as IPv6 (which uses SLAAC) is slowly being adopted, this will probably change in a near or distant future.



From:

<https://wiki.oscardegroot.nl/> - HomeWiki

Permanent link:

<https://wiki.oscardegroot.nl/doku.php?id=networking:debian-networking&rev=1697277161>

Last update: **2023/10/14 09:52**

